

Switch Adapted Toy Manual



What you'll need

- **Bubble blower**
- **Long Phillips screwdriver**
- **Power drill and zip tie**
- **Wire cutter / stripper**
- **Stereo extension cable 3.5mm**
- **Soldering kit or hot glue gun**
- **Hot glue gun**
- **Switch to test finished toy**

1 Unbox toy

Test the toy to make sure it works. You will need a screwdriver to get to the batteries and open the toy.



@AACforALL

2 Unscrew

Unscrew the following screws on the back of the toy. There are two on the side not within the picture



3 Take apart

1. Remove the base and the front.



2. Separate the motor from the back.



3. Locate the two red wires coming from the on/off.



4 Wire stripping

1. Locate port end .



2. Cut the wire.



3. Leave about 3-4 inches of cord.



4. Strip the wire at a 12.



5. Three wires should be exposed.



6. Cut off the yellow wire.



7. Strip two wires to expose copper .



8. Final product .



5 Drill a hole


1. Drill a hole in the toy.



2. Place in the stereo extension cable with the port side on the outside of the toy.




3. Secure with a zip tie on the inside of the toy.



6 Toy Wire Cutting


1. Relocate the two red wires coming from the off and on button.



2. Cut the wires closer to the activation button.



3. Strip the top of each wire to expose copper.




5. Take your stereo extension cable.



6. Take one side of the stereo extension cable and twist with one side of the toy.



7. Twist the other side of the stereo extension cable with the other toy wire.




7 Soldering

1. Grab your soldering tools. If you don't have soldering tools, you can use a hot glue gun.



2. Solder or hot glue each side of the connected wires to secure.



8 Secure

Secure soldered wires with hot glue, keeping each set separate from each other. You can also use electrical tape. This will prevent the toy from activating if the wires touch.



9 Testing station



10 Secure



Secure the toy by placing the screws back within the toy and tightening with a screwdriver. Do the same with the battery compartment.

Finish!

